

Improved
NEW
formula

- ✓ Very low in odour
- ✓ Free from cobalt and ketoximes
- ✓ High wear and water resistance
- ✓ Wide array of colours



Bona Hard Wax Oil

Tough protection made sustainable



Bona Hard Wax Oil

Tough protection made sustainable

For long-lasting protection on floors, Bona Hard Wax Oil delivers excellent resistance to wear, scuff marks and moisture. It produces the warm look of an oiled floor while establishing a hardwearing and stain resistant surface that is spot-repairable and easy to maintain.

The Bona Hard Wax Oil is a balanced blend of natural oils, modified for superior protection of wooden floors. It is extremely low in odour and free from hazardous agents such as cobalt and ketoximes (2-butanoxime, butoxime, MEKO). It is easy to handle and applicable with a roller, brush and trowel. It leaves an open, breathing surface that reduces the risk of side bonding. Highly suitable for floors with underfloor heating.

Used alone

- Bona Hard Wax Oil •
- Bona Hard Wax Oil •
- Bare Wood •

Effects with Bona Oil System

- Bona Hard Wax Oil •
- Bona Craft Oil •
- (Bona Rich Tone) •
- Bare Wood •



Application

For enhanced protection on untreated wood, apply 2 layers of Bona Hard Wax Oil. If you would like to have a special colour effect to express your unique character, combine it with Bona Craft Oil and/or Bona Rich Tone. Apply with roller, brush or stainless steel trowel.

Available in 2 sheens: *Matt and Silk matt*

Key Benefits

- Very low in odour and free from hazardous agents such as cobalt and ketoximes
- High resistance to wear, scuff marks and moisture
 - Seeps into the wood while creating a protective layer
- Easy handling and application with roller, brush or trowel
- High degree of saturation for fast surface treatment
 - High coverage rate
- Enhances the grain and colour of the wood
- Open, breathing surface – Inhibits side-bonding

Technical Data

Base:	Modified hardening oil and wax
Gloss levels:	Matt and Silk matt
Drying time:	– Before sanding/recoating: 6–8 hours* – Light use: min. 18 hours*
	*under normal, ventilated climate conditions, 20°C/60% R.H.
Coverage:	20–24 m ² per litre and coat.
Pack size:	1, 2.5 and 10 litres



Part of the Bona Oil System